



# BREAKERS

## STANDARD FAMILY CODE IR 4000 SERIES VV

Mounting Position	Vertical
Control Voltage Rating Uc [Vdc]	24 - 36 - 48 - 72 - 110 <sup>1</sup>
Auxiliary Contact Blocks	5a1 + 6b0
Block Type	Reed
Arc chute Material	Ceramic
Main Contacts tips Material	AgSnO <sub>2</sub>
Arcing Contacts tips Material	AgW
Electric Diagram HC	42870635C
Layout Drawing HC	42870687C

Commercial Code			
Voltage	Holding System	Thermal Current	
		3000 A	4500 A
1800 V	Holding Coil	<b>IR 4030 VV 18M</b>	<b>IR 4045 VV 18M</b>
3600 V		<b>IR 4030 VV 36M</b>	<b>IR 4045 VV 36M</b>



**MICROELETTRICA**

## Description

DC single pole, magnetic blowout, trip free, air circuit breaker. The closing mechanism is motor-operated independent type while the holding mechanism is magnetic type, provided with holding coil. The breaker is equipped with a direct acting over-current trip device, which may be either unidirectional or bi-directional. Reference standard IEC 60077.

Insulation Characteristics	18M	36M
Rated Operational Voltage $U_{Ne}$ [V <sub>dc</sub> ] <sup>1</sup>	1800	3600
Max Operational Voltage [V <sub>dc</sub> ]	2000	4000
Rated Insulation Voltage [V <sub>dc</sub> ]@ OV4 /PD3A	3700	3700
Rated Insulation Voltage [V <sub>dc</sub> ]@ OV3 /PD3	4800	4800
Electrical Characteristics	18M	36M
Conventional Free Air Thermal Current [A] at 40°C <sup>2</sup>	3000 / 4500 <sup>1</sup>	
Rated Short Circuit Making and Breaking Capacity / Time constant [kA/ms]		
$\tau$ 1	100 / 0 (peak 140 kA)	55 / 0 (peak 77 kA)
$\tau$ 2	60 / 15	50 / 15
$\tau$ 3	50 / 40	50 / 30
$\tau$ 4	35 / 100	50 / 50
Rated Duty Cycle	0-20s-CO-60s-CO	
Peak arc voltage [ $\dot{U}_{arc}$ ]	up to 3 x $U_{Nm}$	
Standard direct acting trip device [kA] <sup>1</sup>		
Setting Range A1	0.9 ÷ 1.5	
Setting Range A2	1.4 ÷ 2.7	
Setting Range A3	2 ÷ 3.4	
Setting Range A4	2.8 ÷ 4.7	
Blow Out Circuit Type	Coil	
Mechanical Characteristics		
Mechanical Endurance (cycles)	6x50000	
Electrical durability [In @ Un]	4x200	
Shock and Vibrations (IEC61373)	Cat.1 - Class B	
Weight [kg] for 3000 [A] / for 4500 [A]	173 / 180	
Control Circuit		
Control Voltage Range	0.7U <sub>c</sub> ÷ 1.25U <sub>c</sub>	
Operated by	D.C. Motor	
Holding closed by	Holding Coil	
Peak closing power and time [W x s]	500 x 0.01	
Nominal closing power and time [W x s]	360 x 1.5	
Holding Coil version		
Nominal holding power @ 20°C [W]	50	
Nominal opening power @ 20°C [W]	0	
Controlled opening time [ms]	< 50	
Auxiliary Circuit		
Type	Reed Contacts (Vacuum Technology)	
Voltage [V <sub>dc</sub> ]	24 / 36 / 48 / 72 / 110 <sup>1</sup>	
Rated Current [A]	5	
Maximum Breaking Power with Inductive Load $\tau=2ms$ [W]	120	
Maximum Breaking Current with Inductive Load $\tau=2ms$ [A]	3	
Maximum Breaking Voltage with Inductive Load $\tau=2ms$ [V]	250	
Minimum let-through Current at 24V <sub>dc</sub> [mA]	5	
Electrical Connections	Fast-on 2.5 x 0.8mm or customized LV Connection <sup>1</sup>	

