



SWITCHES

STANDARD FAMILY CODE N0001250P1B01

Type	N 1250
Number of Poles	1 NC
Connection between poles	None
Mounting Position	Vertical
Control Voltage Rating Uc [Vdc]	110Vdc/Vac - 220Vdc/Vac
Auxiliary Contact Blocks	5 NO + 5 NC
Block Type	B
Arc chute Material	Ceramic in plastic shells
Main Contacts tips Material	S4
Arcing Contacts tips Material	-
Electric Diagram	TU0165/B (DC) - TU0165/C (AC)
Layout Drawing	D53548

¹ To be specified in order phase.



MICROELETTRICA

Description

Contactors with single interruption in air, electromagnetic control by power-save system (economy resistor). Typical application control of all type of motor for standard or severe duty application. Control of resistive, inductive and capacitive circuits: heating, lighting, $\cos\Phi$ rectification, normal stand-by. Reference Standard IEC 60947-4-1.

Electrical Characteristics				
Rated Operational Voltage Ue [Vac/Vdc]	220	380	440	600
Rated Insulation Voltage Ui [Vdc]	1000			
Conventional Free air thermal current Ith [at 40°C] ²	1250			
Conventional Free air thermal current Ith [at 60°C] ²	1100			
Maximum Making Capacity for 100 ms Ich [kA]	18			
Short Circuit Withstand Current for 100 ms Icw [kA]	18			
Average impedance per pole at 50 Hz [MicroOhm]	450			
Blow out circuit type	Direct			
Electrical Characteristics 1NC pole (S6) for DC application				
Rated Operational Voltage [Vdc]	220	380	440	600
Maximum Breaking Capacity tau=15ms Idcmax [A]	4500	3450	3000	2100
Utilization Category according to IEC60947-4-1: DC1&DC3				
Rated Power Pe [kW]	2200	1280	1100	810
Rated breaking Current Ie [A]	1230	630	550	340
Electrical Characteristics 1NC pole (S6) for AC application				
Rated Operational Voltage [Vac]	220	380	440	600
Maximum Breaking Capacity $\cos\Phi=0,5$ Iacmax [A]	6500	3750	3250	2350
Utilization Category according to IEC60947-4-1: AC1&AC2&AC3				
Rated Power Pe [kW]	215	215	215	215
Rated Making and breaking Current Ie [A]	700	400	350	255
Utilization Category according to IEC60947-4-1: AC4				
Rated Power Pe [kW]	170	170	170	170
Rated Making and breaking Current Ie [A]	560	325	280	210

² Device cabled according IEC 60947 ⁴ Other mounting positions not allowed

Minimum clearances [mm] from:				
Rated Insulation Voltage		X	Y	Z
1000	Metal Parts	100	50	30
	Plastic Parts	50	30	20



